

DS-PWA48-E-WB AX PRO

AX PRO supports Wi-Fi, TCP/IP communication methods. It also supports Hik-ProConnect, Hik-Connect, Hik IP Receiver, Hik IP Receiver Pro and Hik-Central, which is applicable to the scenarios of market, store, house, factory, warehouse, office, etc.



Key Feature

- TCP/IP, Wi-Fi
- New generation wireless protocol: Tri-X/Cam-X
- Long RF transmission distance
- Two-way communication with AES-128 encryption
- Connects up to 48 wireless zones/outputs (including 48 PIRCAMs), 16 wireless keyfobs, 2 repeaters, 4 sounders, 8 tag readers & keypads, and 48 PIRCAMs.
- Supports up to 16 network users, including 1 installer, 1 administrator, and 14 normal users
- Voice prompt
- Configuration via Web client, mobile client, and Convergence Cloud
- Hik-Connect and Hik-ProConnect configuration depends on the user access level
- Views live videos from Hik-Connect
- Alarm video clips via emails and APP
- Uploads alarm reports to ARC
- Supports LED indicator to indicates system status
- 4520 mAh lithium backup battery
- SIA-DC09 protocol, and supports both Contact ID and SIA data format
- Supports Hik-IP Receiver and Hik-IP Receiver Pro for ARC communication

Available Model

DS-PWA48-E-WB





Specification

| | | AX PRO E |
|-----------------------|-----------------------------------|---|
| Basic | Frequency | 433Mhz |
| | Wireless type | 2-way wireless |
| | Wireless Security | Frequency Hoping 128 AES Encryption |
| | Wireless Zones | Up to 48 (Up to 48 PIRCAMs) |
| | Wireless Outputs | |
| | Wireless Tag Readers & Keypads | Up to 8 |
| | Wireless Sounders | 4 |
| | Wireless Keyfobs | 16 |
| | Wireless Repeaters | 2 |
| | Tags | 16 |
| | PIRCAM | Supported |
| | Onboard IP CAMERA Integration | 2*7s clips have their own storage, not overrides each other |
| User | Installer | 1 |
| | Admin | 1 |
| | Users | 14 |
| | Areas | 8 |
| | Voice prompt | Supported |
| | Loudspeaker built in | Supported |
| | Tag reader built in | N/A |
| | LEDs Status | Arm/Disarm, Alarm, Tamper, Fault, Cloud, Power |
| | Memory Log stored | 5000 |
| Key Software Features | RS-232 output | Supported |
| | Programming tools | Hik-Connect/Hik-ProConnect/Web Portal/ IVMS4200/ Convergence Cloud |
| | Firmware upgrade | APP Manual or Web |
| | Arm Modes | Away/Stay |
| | Automatic Arm/Disarm Timers | Supported |
| | Forced Arming with Open Zones | Supported |
| | Diagnostics of via the APP or Web | Supported |
| Communication | LAN port | Supported |
| | Wi-Fi on board | Supported(2.4G) |
| | GPRS on board | N/A |
| | 3/4G on board | N/A |



| | SIM slot | N/A |
|------------|--|---|
| | SMS notification | N/A |
| | Alarm voice call | N/A |
| | | SIA DC09(SIA level 2, Contact ID), ISUP, ISAPI (SDK) |
| | ARC protocol | Hik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) |
| | | Supports video verification and remote control |
| | User APP for operating | Supported |
| | Installer APP for programming | Supported |
| | Web server for maintenance (offline configuration) | Supported |
| Hardware | Battery Stand by | 12 hours |
| | Power Supply | Built in power supply |
| | Battery pack | Built in on board Battery Li |
| | Housing | Plastic |
| Automation | Schedules | Wall switch & Relay & Plug (Has time schedule) |
| Approvals | CE/CB | Supported |
| | Rohs/Reach/WEEE | Supported |
| | FCC | Supported |
| | RCM | Supported |
| Others | Operation temperature | -10 °C to +55 °C |
| | Dimension(W x H x D) | 170.0 mm (6.7") x 170.0 (6.7") mm x 38.6 mm (1.5") |
| | Weight | 557.5 g(19.7 oz) |



Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400

sales.usa@hikvision.com **Hikvision Australia** T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T+01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33[0]1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-[0]31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com